

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 442 light grey

UFI: Y25F-J0MR-4006-P6NX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Company name:	DINOL GmbH	
Street:	Pyrmonter Strasse 76	
Place:	D-32676 Luegde	
Telephone:	+ 49 (0) 5281 982980	Telefax: + 49 (0) 5281 9829860
e-mail:	msds@dinol.com	
Contact person:	Labor	
Responsible Department:	msds@dinol.com	

1.4. Emergency telephone number: Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
 Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Skin Sens. 1; H317
 STOT SE 3; H335
 STOT RE 2; H373
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

xylene
 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
 Fatty acids, C18-unsatd. , trimers, compds. with oleylamine
 Fatty acids, tall-oil, compds. with oleylamine
 Cobalt bis(2-ethylhexanoate)

Signal word: Warning

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 2 of 18

H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378	In case of fire: Use water to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Restricted to professional users.
--------	---

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H317-H412

Precautionary statements

P280

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 3 of 18

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			20 - < 25 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
123-86-4	n-butyl acetate			5 - < 10 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			5 - < 10 %
	919-446-0	649-330-00-2	01-2119458049-33	
	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066			
1330-20-7	xylene			1 - < 5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
13463-67-7	Titanium dioxide			1 - < 5 %
	236-675-5			
108-65-6	2-methoxy-1-methylethyl acetate			1 - < 5 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
147900-93-4	Fatty acids, C18-unsatd. , trimers, compds. with oleylamine			< 1 %
	604-612-4			
	Acute Tox. 4, Skin Sens. 1, STOT RE 2, Aquatic Chronic 2; H302 H317 H373 H411			
85711-55-3	Fatty acids, tall-oil, compds. with oleylamine			< 1 %
	288-315-1		01-2119974148-28	
	Eye Dam. 1, Skin Sens. 1A, STOT RE 2; H318 H317 H373			
136-52-7	Cobalt bis(2-ethylhexanoate)			< 0.1 %
	205-250-6		01-2119524678-29	
	Repr. 1B, Eye Irrit. 2, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 3; H360F H319 H317 H400 H412			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	20 - < 25 %
		inhalation: LC50 = 10-20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 8700 mg/kg	
123-86-4	204-658-1	n-butyl acetate	5 - < 10 %
		inhalation: LC50 = >21 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 8800 mg/kg	
	919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	5 - < 10 %
		dermal: LD50 = >3400 mg/kg; oral: LD50 = >15000 mg/kg	
1330-20-7	215-535-7	xylene	1 - < 5 %
		inhalation: LC50 = 20 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 4300 mg/kg	
13463-67-7	236-675-5	Titanium dioxide	1 - < 5 %
		dermal: LD50 = > 10000 mg/kg; oral: LD50 = > 20000 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	1 - < 5 %
		inhalation: LC50 = 35,7 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 8500 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
147900-93-4	604-612-4	Fatty acids, C18-unsatd. , trimers, compds. with oleylamine	< 1 %
		oral: LD50 = > 1570 mg/kg	
85711-55-3	288-315-1	Fatty acids, tall-oil, compds. with oleylamine	< 1 %
		oral: LD50 = > 2000 mg/kg	
136-52-7	205-250-6	Cobalt bis(2-ethylhexanoate)	< 0.1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 3129 mg/kg	

Further Information

The homogeneous mixing of this product is controlled by continuous physical tests. Formerly dusty raw materials are completely integrated into the liquid/pasty mass. Possible AGW-values for solid substances are therefore not given, as there is no longer any risk of inhalation of these substances (when handling this mixture).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 5 of 18

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Dizziness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 6 of 18

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect from direct sunlight.

Hints on joint storage

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 7 of 18

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 8 of 18

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1330-20-7	xylene			
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	77 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m ³
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	480 mg/m ³
Worker DNEL, acute		inhalation	systemic	960 mg/m ³
Worker DNEL, long-term		inhalation	local	480 mg/m ³
Worker DNEL, acute		inhalation	local	960 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	102,34 mg/m ³
Consumer DNEL, acute		inhalation	systemic	859,7 mg/m ³
Consumer DNEL, long-term		inhalation	local	102,34 mg/m ³
Consumer DNEL, acute		inhalation	local	859,7 mg/m ³
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Worker DNEL, long-term		inhalation	systemic	330 mg/m ³
Worker DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	71 mg/m ³
Consumer DNEL, long-term		dermal	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	289 mg/m ³
Worker DNEL, acute		inhalation	local	174 mg/m ³
Worker DNEL, long-term		inhalation	systemic	77 mg/m ³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	174 mg/m ³
Consumer DNEL, acute		inhalation	local	174 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m ³
,				
100-41-4	ethylbenzene			
Worker DNEL, long-term		inhalation	systemic	77 mg/m ³
Worker DNEL, acute		inhalation	local	293 mg/m ³
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	15 mg/m ³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
,				

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 9 of 18

PNEC values

CAS No	Substance	
Environmental compartment		Value
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
100-41-4	ethylbenzene	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		13,7 mg/kg
Marine sediment		1,37 mg/kg
Secondary poisoning		0,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		9,6 mg/l
Soil		2,68 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN 166)

Hand protection

Tested protective gloves must be worn (EN ISO 374):

FKM (fluoro rubber), Breakthrough time:: 480 min.

PVA (Polyvinyl alcohol), Breakthrough time:: 480 min.

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 10 of 18

NBR (Nitrile rubber), Breakthrough time:: 30 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

gas filtering equipment (EN 141)., Filter material/medium: A/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	light grey
Odour:	characteristic
Odour threshold:	not determined

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	124 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	24 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

not determined

Lower explosion limits:	1,0 vol. %
Upper explosion limits:	7,0 vol. %
Auto-ignition temperature:	210 °C

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

pH-Value: not applicable

Viscosity / dynamic:
(at 20 °C) 1600-2200 mPa·s

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure:
(at 20 °C) 6,0 hPa

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 11 of 18

Density (at 20 °C): 1,18-1,22 g/cm³
Relative vapour density: not determined

9.2. Other information**Information with regard to physical hazard classes**

Oxidizing properties
not determined

Other safety characteristics

Solvent separation test: not determined
Solvent content: 44,4 %
Solid content: 53-57 %
Evaporation rate: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 12 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 mg/kg 8700	Rat		
	dermal	LD50 mg/kg 2000	Rabbit		
	inhalation (4 h) vapour	LC50 mg/l 10-20	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg 8800	Rat		
	dermal	LD50 mg/kg > 5000	Rabbit		
	inhalation (4 h) dust/mist	LC50 >21 mg/l	Rat		
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50 mg/kg >15000	Rat		
	dermal	LD50 mg/kg >3400	Rat		
1330-20-7	xylene				
	oral	LD50 mg/kg 4300	Rat		
	dermal	LD50 mg/kg 2000	Rabbit		
	inhalation (4 h) vapour	LC50 20 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
13463-67-7	Titanium dioxide				
	oral	LD50 mg/kg > 20000	Rat		
	dermal	LD50 mg/kg > 10000	Rabbit		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 mg/kg 8500	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
	inhalation (4 h) vapour	LC50 35,7 mg/l	Rat		
100-41-4	ethylbenzene				
	oral	LD50 mg/kg 3500	Rat	GESTIS	
	dermal	LD50 mg/kg 15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
147900-93-4	Fatty acids,C18-unsatd. , trimers, compds. with oleylamine				
	oral	LD50 mg/kg > 1570	Rat		

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 13 of 18

85711-55-3	Fatty acids, tall-oil, compds. with oleylamine				
	oral	LD50 mg/kg	> 2000	Rat	
136-52-7	Cobalt bis(2-ethylhexanoate)				
	oral	LD50 mg/kg	3129	Rat	
	dermal	LD50 mg/kg	>2000	Rat	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Fatty acids, C18-unsatd. , trimers, compds. with oleylamine; Fatty acids, tall-oil, compds. with oleylamine; Cobalt bis(2-ethylhexanoate))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 14 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 86 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 2-8 mg/l		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l 1-10	48 h			
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 62 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 674 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia magna (Big water flea)		
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LL50 mg/l 10-30	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 4,6 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EL50 mg/l 10-22	48 h	Daphnia magna (Big water flea)		
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 80 mg/l	96 h	fish	GESTIS	
	Acute algae toxicity	ErC50 5 mg/l	72 h	alga	GESTIS	
	Acute crustacea toxicity	EC50 mg/l 4,75	48 h		GESTIS	

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
		74,7 %	28	
	Leicht biologisch abbaubar			
108-65-6	2-methoxy-1-methylethyl acetate			
	OECD 302 B	>90 %		
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 15 of 18

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	2,3
1330-20-7	xylene	3
108-65-6	2-methoxy-1-methylethyl acetate	0,56
100-41-4	ethylbenzene	3,15

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	25,9	Oncorhynchus mykiss (Rainbow trout)	

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1139
14.2. UN proper shipping name:	Coating solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 16 of 18



Classification code: F1
Special Provisions: 640E
Limited quantity: 5 L
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Other applicable information (land transport)

E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: no
Special Provisions: 955
Limited quantity: 5 L
EmS: F-E, S-E

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

E1

Passenger-LQ: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 17 of 18

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2004/42/EC (VOC): 44,4 %

528 g/l

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,9,15.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to UK REACH Regulation

DINITROL 442 light grey

Revision date: 19.10.2021

Product code: 5114

Page 18 of 18

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)